

DECLARATION OF PERFORMANCE

No.: 64217-a-CPR_2014.12.1

Unique identification code of the product-type	64217 – Eurothane GK +
Intended use/es	Thermal insulation for buildings
Manufacturer	Recticel NV - Tramstraat 6 - B-8560 Wevelgem
System/s of AVCP	AVCP 3
Harmonised standard	EN 13165:2012
Notified body/ies	Notified testing laboratory No. NB 1173, NB 0071 & NB 1136 determined the production type under system AVCP3.

Essential characteristics	Performance	
	(The letters 'NPD' (No Performance Determined) are indicated where no performance is declared.)	
Reaction to fire	Reaction to fire	D-S2-d0
Reaction to fire – end use	Reaction to fire – end use	NPD
Thermal resistance	Thermal resistance (R ₀ in m ² K/W)	0,80 for d _N 20mm 6,65 for d _N 160mm
	Thermal conductivity (λ _D in W/mK)	0,024
Thickness	d _N : 20-160 mm	T2
Compressive strength	CS(10/Y)150	
Tensile strength/shear behaviour	Tensile strength perpendicular to faces:	TR80
	Shear strength:	NPD
	Shear modulus:	NPD
Water permeability	Water absorption	
	- short term by partial immersion	NPD
	- long term by partial immersion	NPD
	- long term by total immersion	WL(T)2
	Flatness after one-sided wetting	NPD
Water vapour permeability	Water vapour transmission	NPD
Acoustic absorption index	Sound absorption	NPD
Direct airborne sound insulation index	Sound absorption	NPD
Continuous glowing combustion	No harmonized test method available	
Release of dangerous substances to the indoor environment	No harmonized test method available	
Durability of reaction to fire against heat, weathering, ageing / degradation	Reaction to fire does not change with time	
Dimensional stability under specified temperature and humidity conditions	48h, 70°C, 90% R.H.	DS(70,90)3
	48h, -20°C	DS(-20,-)1
Deformation under specified compressive load and temperature conditions	40 kPa, 70°C, 168h	DLT(2)5
Compressive creep		NPD

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/211, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Wim Giebels – Industrial Manager Recticel Building Insulation
at Wevelgem on December 1st 2014

YDEEVNEDEKLARATION

No.: 64217-a-CPR_2014.12.1

Varetypens unikke identifikationskode	64217 – Eurothane GK +
Byggevaarens	Varmeisolering til bygninger
Fabrikantens navn	Recticel NV - Tramstraat 6 - B-8560 Wevelgem
System eller systemer til vurdering	AVCP 3
Harmoniseret standard	EN 13165:2012
Notificerede prøvningslaboratorium	Det notificerede prøvningslaboratorium nr. NB 1173, NB 0071 og NB 1136 udarbejdede prøvningsrapporterne om de opgivne egenskaber i henhold til system AVCP3.

Afgørende egenskaber	Præstation	
	(Bogstaverne NPD (No Performance Determined) er anført i tilfælde hvor præstationerne ikke er deklarerede)	
Reaktion ved brand	Reaktion ved brand	D-S2-d0
Reaktion ved brand – endelig anvendelse	Reaktion ved brand – endelig anvendelse	NPD
Termisk modstand	Termisk modstand (RD i m ² K/W)	0,80 for d _N 20mm 6,65 for d _N 160mm
	Varmeledningsevne (?D i W/mK)	0,024
Tykkelse	d _N : 20-160 mm	T2
Trykstyrke	CS(10Y)150	
Egenskaber vedrørende trækbrudstyrke/forskydning	Trækbrudstyrke vinkelret på flader: Forskydningsstyrke: Forskydningsmodul:	TR80 NPD NPD
Vandgennemtrængelighed	Vandabsorption - kort tid ved delvis nedsækning - lang tid ved delvis nedsækning - lang tid ved fuldstændig nedsækning Fladhed efter ensidet befugtning	NPD NPD WL(T)2 NPD
Vanddampgennemtrængelighed	Vanddamptransmission	NPD
Akustisk absorptionsindeks	Lydabsorption	NPD
Direkte luftbåren lydisolationsindeks	Lydabsorption	NPD
Kontinuerlig glødebrand	Der er ingen tilgængelig harmoniseret prøvningsmetode	
Emission af farlige stoffer til indemiljøet	Der er ingen tilgængelig harmoniseret prøvningsmetode	
Ældning af reaktion ved brand ift. varme-, vejrpåvirkning, aldring / nedbrydning	Reaktionen ved brand ændres ikke med tiden	
Dimensionsstabilitet under specificerede temperatur- og fugtforhold	48t, 70°C, 90% R.H.	DS(70,90)3
	48t, -20°C	DS(-20,-)1
Deformering under specificerede trykbelastnings- og temperaturforhold	40 kPa, 70°C, 168t	DLT(2)5
Kompressionskrybning		NPD

Det ovennævnte produkts præstationer er i overensstemmelse med de anførte præstationer.

Denne præstationserklæring er udstedt i overensstemmelse med Forordning (EU) Nr. 305/211, under ovennævnte fabrikants eksklusive ansvar.

Underskrevet for og på vegne af producenten af :

Wim Giebens – Industrial Manager Recticel Building Insulation
at Wevelgem on December 1st 2014