## **DECLARATION OF PERFORMANCE**

No.: 64685-a-CPR\_2014.12.1

Unique identification code of the product-type	64685 - Eurothane Eurodeck	
Intended use/es	Thermal insulation for buildings	
Manufacturer	Recticel Ltd Enterprise Way, Meir Park - Stoke-On-Trent, ST3 7UN - UK	
System/s of AVCP	AVCP 3	
Harmonised standard	EN 13165:2012	
Notified body/ies	Notified testing laboratory No. NB 0836 determined the production type under system AVCP3.	

Essential characteristics	Performance (The letters 'NPD' (No Performance Determined) are indicated where no performance is declared.)		
Reaction to fire	Reaction to fire	F	
Reaction to fire – end use	Reaction to fire – end use	NPD	
Thermal resistance	Thermal resistance (R <sub>D</sub> in m²K/W)	1,35 for d <sub>N</sub> 30mm 7,25 for d <sub>N</sub> 160mm	
	Thermal conductivity (λ <sub>D</sub> in W/mK)	0,022	
Thickness	d <sub>N</sub> : 30-160 mm	T2	
Compressive strength	CS(10/Y)150		
Tensile strength/shear behaviour	Tensile strength perpendicular to faces: Shear strength: Shear modulus:	NPD NPD NPD	
Water permeability	Water absorption - short term by partial immersion - long term by partial immersion - long term by total immersion Flatness after one-sided wetting	NPD NPD NPD NPD	
Water vapour permeability	Water vapour transmission	NPD	
Acoustic absorption index	Sound absorption	NPD	
Direct airborne sound insulation index	Sound absorption	NPD	
Continuous glowing combustion	No harmonized test method available		
Release of dangerous substances to the indoor environment	No harmonized test method available		
Durability of reaction to fire against heat, weathering, ageing / degradation	Reaction to fire does not change with time		
Dimensional stability under specified temperature and humidity conditions	48h, 70°C, 90% R.H.	NPD	
	48h, -20°C	NPD	
Deformation under specified compressive load and temperature conditions	40 kPa, 70°C, 168h	NPD	
Compressive creep		NPD	

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/211, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Wim Giebens – Industrial Manager Recticel Building Insulation at Wevelgem on December 1st 2014