

DECLARATION OF PERFORMANCE

No.: **64684-a-CPR_2016.09.1**

Unique identification code of the product-type	SL BASEBOARD
Intended use/es	Thermal insulation for buildings
Manufacturer	Recticel Ltd. – Enterprise Way, Meir Park – Stoke-On-Trent, ST3 7UN - UK
System/s of AVCP	AVCP 3
Harmonised standard	EN 13165:2012 + A2:2016
Notified body/ies	Notified testing laboratory No. NB 0836 determined the production type under system AVCP3.

Essential characteristics	Performance	
	(The letters 'NPD' (No Performance Determined) are indicated where no performance is declared.)	
Reaction to fire	Reaction to fire	F
Reaction to fire – end use	Reaction to fire – end use	NPD
Thermal resistance	Thermal resistance (R_D in m ² K/W)	2,00 for d_N 45mm 4,05 for d_N 90mm 4,50 for d_N 100mm 5,45 for d_N 120mm
	Thermal conductivity (λ_D in W/mK)	0,022
Thickness	d_N : 25-160 mm	T2
Compressive strength	CS(10/Y)120 for $d_N < 50$; CS(10/Y)140 for $d_N 50-160$ mm	
Tensile strength/shear behaviour	Tensile strength perpendicular to faces:	NPD
	Shear strength:	NPD
	Shear modulus:	NPD
Water permeability	Water absorption	NPD
	- short term by partial immersion	NPD
	- long term by partial immersion	NPD
	- long term by total immersion	NPD
	Flatness after one-sided wetting	NPD
Water vapour permeability	Water vapour transmission	NPD
Acoustic absorption index	Sound absorption	NPD
Direct airborne sound insulation index	Sound absorption	NPD
Continuous glowing combustion	No harmonized test method available	
Release of dangerous substances to the indoor environment	No harmonized test method available	
Durability of reaction to fire against heat, weathering, ageing / degradation	Reaction to fire does not change with time	
Dimensional stability under specified temperature and humidity conditions	48h, 70°C, 90% R.H.	NPD
	48h, -20°C	NPD
Deformation under specified compressive load and temperature conditions	40 kPa, 70°C, 168h	NPD
Compressive creep		NPD

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/211, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

at Wevelgem on September 1st 2016

Wim Giebens – Industrial Manager Recticel Building Insulation